LED海报屏“第一品牌”
LED Electronic Poster Screen "First Brand"

三折叠(双面)LED海报屏 独家方案

Exclusive solution for three fold (double-sided) LED poster screen

专利技术 仿冒必究

Patent technology counterfeiting will be prosecuted

产品特点

Product features

◆ 拥有20年的行业经验，始终以用户为中心，通过大量的用户反馈和市场调研，深度挖掘并解决用户在LED显示屏使用中的痛点问题。例如，针对传统LED显示屏安装难、程序调试复杂、不便运输等难点，我司在2024年率先推出了折叠式LED电子海报屏，赢得了用户及业界的高度认可。

◆ 我司又在2025年3月又推出了”三折叠（双面）LED移动海报屏，2025年3月第一次在深圳福永ISLE展会上亮相，获得了不少用户的高度关注。

◆ 专利产品，独家技术。

◆ “一屏两显”，展开就是一块大屏，折叠起来秒变双面屏。

◆ 私模设计，外观精美，机身采用航空铝材料，自身散热效果好,50ｍｍ超薄机身，双面仅110ｍｍ 78KG超轻机身。

◆ 无需专业技术人员安装，通电即可使用。

◆ APP无线发布内容，便捷式操作，内容一件传输。

◆ 快速锁设计，小白便能轻松驾驭，支持多台快速无缝拼接。

◆ 支持同步，异步，可用于高清电子海报，也可同步显示高清宣传片，会议PPT，直播背景等，用途广泛。

◆ SMD灯珠采用了“地砖级”GOB工艺，防刮伤，防掉灯，表面防溅水，防潮，使用更加稳定。

◆ 自带4个万向轮，轻松移动，想放哪里就放哪里。

◆ With 20 years of industry experience, always putting users at the center, deeply exploring and solving pain points for users in the use of LED displays through extensive user feedback and market research. For example, in response to the difficulties of traditional LED display installation, complex program debugging, and inconvenient transportation, our company took the lead in launching a foldable LED electronic poster screen in 2024, which has won high recognition from users and the industry.

◆ Our company launched the "Three Fold (Double sided) LED Mobile Poster Screen" in March 2025, which made its debut at the Shenzhen Fuyong ISLE exhibition and received high attention from many users.

◆ Patent products, exclusive technology.

◆ "One screen, two displays", unfolded to form a large screen, folded to instantly become a double-sided screen.

◆ Private mold design, exquisite appearance, aircraft aluminum material body, good heat dissipation effect, 50mm ultra-thin body, double-sided only 110mm. 78KG ultra light body.

◆ No need for professional technicians to install, can be used with power on.

The APP wirelessly publishes content, with convenient operation and one piece transmission of content.

◆ Quick lock design, easy for beginners to control, supports seamless splicing of multiple devices quickly.

◆ Supports synchronization and asynchrony, can be used for high-definition electronic posters, as well as synchronously displaying high-definition promotional videos, conference PPTs, live streaming backgrounds, etc., with a wide range of applications.

◆ The SMD lamp beads adopt the "tile level" GOB process, which is scratch resistant, anti drop, surface splash resistant, moisture-proof, and more stable to use.

◆ Equipped with 4 swivel wheels, easy to move and place wherever you want.

三折叠（双面）LED海报屏参数表“四款不同清晰度”

Three fold (double-sided) LED poster screen parameter table "four different clarity"

名称 Name	**项目** Project	**P2.5**	**P1.86**	**P1.53**	**P1.25**
显示模块参数 Display module parameters	像素点间距 Pixel spacing	2.5mm	1.86mm	1.538mm	1.25mm
	像素构造 Pixel construction	表贴三合一LED	表贴三合一LED	表贴三合一LED	表贴三合一LED
	模组分辨率 Resolution ratio	128*(h)64点	172*(h)86点	204*(h)104点	256*(h)128点
	模组尺寸 Module Size	(w)320*(h)160mm	(w)320*(h)160mm	(w)320*(h)160mm	(w)320*(h)160mm
	防护工艺 Protective technology	GOB	GOB	GOB	GOB
	模组重量 Module weight	0.55kg	0.55kg	0.55kg	0.55kg

整机组成 Whole machine composition	整机模组组成 Whole machine module composition W*H	(w)4* (H) 12张	(w)4* (H) 12张	(w)4* (H) 12张	(w)4* (H) 12张
	单面显示分辨率 Single sided display resolution W * H	(w)512* (H) 768px	(w)688* (H) 1032px	(w)832* (H) 1248px	(w)1024* (H) 1536px
	双面显示分辨率 Dual sided display resolution W * H	(w)256* (H) 768px	(w)344* (H) 1032px	(w)416* (H) 1248px	(w)512* (H) 1536px
	单面显示尺寸 Single sided display size	1280*1920mm	1280*1920mm	1280*1920mm	1280*1920mm
	双面显示尺寸 Double sided display size	640*1920mm	640*1920mm	640*1920mm	640*1920mm
	单面外观尺寸 Single sided appearance dimensions	1280*2070mm	1280*2070mm	1280*2070mm	1280*2070mm
	双面外观尺寸 Double sided appearance dimensions	640*2070mm	640*2070mm	640*2070mm	640*2070mm
	整机重量 Gross weight of the machine	78kg	78kg	78kg	78kg
光学参数 Optical parameters	平整度 Flatness tolerance	0.5mm	0.5mm	0.5mm	0.5mm
	白平衡亮度 White balanced brightness	600CD	650CD	700CD	750CD
	灰度等级 Gray scale	14-16BT 可调	14-16BT 可调	14-16BT 可调	14-16BT 可调
	色温 Color temperature	3200-9000可调	3200-9000可调	3200-9000可调	3200-9000可调
	最佳视距离 Best visual distance	3-20M	3-20M	3-20M	3-20M
	视角（水平） Perspective (horizontal)	160°	160°	160°	160°
	视角（垂直） Perspective (vertical)	160°	160°	160°	160°
	发光点中心距偏差 Tolerance of center to center distance of luminous point	≤3%	≤3%	≤3%	≤3%
	亮度均匀性 luminance uniformity	≥95	≥95	≥95	≥95
	色度均匀性 Chromaticity uniformity	±0.003Cx,Cy之内	±0.003Cx,Cy之内	±0.003Cx,Cy之内	±0.003Cx,Cy之内
	对比度 contrast ratio	8000:1	8000:1	8000:1	8000:1
通电要求 Power on requirements	供电要求 Power supply requirements	100-240V	100-240V	100-240V	100-240V
	峰值功耗 Peak power consumption	850W	900W	1200W	1600W
	平均功耗 Average Power	220W	300W	400W	565W
通讯参数 Communication parameters	同步/异步 Synchronous/Asynchronous	支持 support			
	通讯方式 Communication method	APP/U盘/网口/4G远程APP/USB drive/Ethernet port/4G remote			
	通讯接口 Interface	JS485*1 WIFI*1 U盘*1 HDMI*2			
扬声器 Speaker	是否内置扬声器 Is there a built-in speaker	50*12mm*2PCS			
	音频接口 audio	3.5音频接口/支持外接功放 3.5 Audio Interface/Supports External Amplifier			
性能处理 Performance processing	驱动方式 Drive mode	恒流驱动 Constant current drive			
	换帧频率 Frame Frequency	60HZ			
	刷新率 Refresh rate	≥3840HZ			

使用参数 Using parameters	寿命典型值 Typical lifespan values	50000H
	工作温度范围 Working temperature range	-40—50°C
	工作湿度范围 Operating humidity range	10-80% 无结露
	存储温度范围 Storage Temperature Range	-50—50RH
	存储湿度范围 Storage humidity range	10-85%RH 无结露

产品尺寸

Product size

三折叠（双面）LED海报屏展示

Three fold (double-sided) LED poster screen display



展开单面外观尺寸：宽度1280*高度2070*厚度50mm

Unfold single-sided appearance dimensions: width 1280 * height 2070 * thickness 50mm



折叠后双面外观尺寸:宽度640*高度2070*厚度110mm

Folding double-sided appearance dimensions: width 640 * height 2070 * thickness 110mm

多角度显示，能满足复杂多变的应用场景

Multi angle display, capable of meeting complex and varied application scenarios



无需安装，通电即用

No installation requiredready to use when powered on

成品发货，无需专业技术安装调试，即插即用

Finished product delivery ho need forinstalland debug.professional technicians toplug and play



采用“地砖级GOB工艺”

Adopting the "floor tile grade GOB process"

表面防溅水，防刮花，放磕碰，防潮，稳定性更好

Surface splash proof, scratch proof, collision proof, moisture-proof, and better stability





支持多台无缝拼接

Support seamless splicing of multiple units

可单台使用，同时也支持多台无缝拼接成一个大屏，应用场景更加广泛

It can be used as a single device and also supports seamless splicing of multiple devices into a large screen, with a wider range of application scenarios



万向轮设计

Universal Wheel Design

自带4个万向轮，移动更方便，想放哪里就放哪里

Comes with 4 swivel wheels, making it easier to move and place wherever you want

手机APP一键发布

One click release of mobile app

支持手机一键上传内容，傻瓜式软件，小白都能轻松操作

Support one click upload of content on mobile phones, a foolproof software that even beginners can easily operate

系统支持同步/异步

The system supports synchronous/asynchronous

异步可脱机循环播放，用于广告宣传
同时也支持同步显示，用于会议，直播等场景

Asynchronous offline loop playback, used for advertising promotion.
It also supports synchronous display for scenarios such as meetings and live broadcasts




支持多种传输方式

Supports multiple transmission methods

设备标配U盘，WiFi，网口，HDMI（选配），无线4G（选配）

The device comes standard with USB flash drive, WiFi, Ethernet port, HDMI (optional), and wireless 4G (optional)

U盘
USB flash drive

网口
Ethernet port

WiFi
WiFi

4G远程
4G remote

高清显示

High definition display

高亮度
high brightness

高色彩还原度
high color reproduction

高对比度
high contrast

应用场景案例展示

Application scenario case presentation



公司前台
Reception

餐饮店
Restaurant

学校
School

舞台
Stage

会议室
Meeting room

服装专卖店
Clothing store

会展展台

Exhibition booth